RCE Paris

1 – 3 novembre 2018

Prétraitement des images APN

Pourquoi un prétraitement des images ?

Parasites contenus sur les images

Bias

Vignetage

Pixels chauds, pixels froids

Poussières sur le capteur

Les parasites contenus dans l'image

=

+

+

Image brute

Signal du Bias
Transfert de données

Bruit thermique
pixels chauds et froids

Défaut d'homogénéité
*défaut d'uniformité du capteur
poussières, interférences*

L 'acquisition des images APN consiste aussi à réaliser des images pour isoler « proprement » les parasites:

- ⦿ Bias ou offset
- ⦿ Signal thermique
- ⦿ Flat ou PLU
- ⦿ Images brutes
- ⦿ Toutes les images en RAW ou RAW+ jpg

Particularités du prétraitement avec PixInsight

- ⦿ Travail en mode linéaire
- ⦿ Calculs et traitement sur les images en 32 bits
- ⦿ STF développement artificiel des niveaux de l'image
- ⦿ Utilisation d'une séquence chronologique des process icons
- ⦿ Paramétrage personnalisé des process icons

Comment réaliser un master bias ?

Comment réaliser un bias :

Bouchon objectif fermé, occultation du viseur ou isoler le boîtier APN sous un tissu noir.

Réaliser une centaine d'images « rapide » ($1/4000^{\text{ème}}$) de seconde à 200 ISO pour isoler le signal de l'offset (bias).

Ces images seront empilées et moyennées pour créer un Master Bias

Cas particulier pour les boîtiers APN à très faible bruit de lecture.

Le master bias ou super bias est propre à chaque boîtier APN, il est stable et reste identique au fil des mois voir des années.

Comment réaliser un master dark ?

- *Comment réaliser un dark :*

Faire une série d'images noires avec le même temps de pose que l'image réelle et dans les mêmes conditions de température ambiante.

Combien d'images ? Le même nombre que les brutes sans dithering, 20 à 30% du nombre des images brutes avec dithering.

Ces images seront ensuite empilées et moyennées pour créer un **Master Dark**

Comment réaliser un master flat ?

- **Comment réaliser un Flat :**
Conserver l'assemblage optique, ne pas modifier la focalisation, faire des images d'une surface avec un éclairage uniforme à 200 ISO. Vérifier la position de l'histogramme. (centre droite)
Empiler et moyenner les images pour créer un **Master Flat**

De la discipline dans les fichiers !

2015_02_09_M42_IU-200@200	10/02/2015 17:36	Dossier de fichiers
2015_02_09_M42_AP160@5.7MII	10/02/2015 15:40	Dossier de fichiers
2015_02_09_M45_AP160@5.7MII	10/02/2015 17:12	Dossier de fichiers
2015_02_09_NGC884-869_70-200@200	10/02/2015 17:24	Dossier de fichiers
2015_02_09_NGC1499_70-200@200	10/02/2015 17:30	Dossier de fichiers
2015_02_09_NGC2237_70-200@200	10/02/2015 17:26	Dossier de fichiers
2015_02_10_Bias_1600iso_MarkIII	01/03/2015 22:06	Dossier de fichiers
2015_02_10_Dark_6400iso_VSD108	26/03/2015 21:38	Dossier de fichiers
2015_02_10_Flat_1600iso_VSD108	26/03/2015 21:11	Dossier de fichiers
2015_02_10_M42_IC434_VSD108	11/02/2015 11:37	Dossier de fichiers
2015_02_10_NGC1499_VSD108	11/02/2015 11:33	Dossier de fichiers
2015_02_10_NGC2237_AP160@5.7	26/04/2015 14:38	Dossier de fichiers
2015_02_10_NGC2237_VSD108	27/03/2015 22:12	Dossier de fichiers
2015_02_11_Jupi_rvb	12/02/2015 12:09	Dossier de fichiers
2015_02_11_M45_VSD108	22/03/2015 21:27	Dossier de fichiers
2015_04_05_Time Lapse	08/04/2015 13:15	Dossier de fichiers
2015_04_07_C11F7_M44	26/04/2015 15:09	Dossier de fichiers
2015_04_07_C11F7_M65_M66	08/04/2015 13:06	Dossier de fichiers
2015_04_07_Jupi	26/04/2015 14:31	Dossier de fichiers
2015_04_21_M51_MarkIII_AP F7.7	24/04/2015 21:56	Dossier de fichiers
2015_04_21_M65_M66_NGC3628_MarkIII_AP F7.7	28/04/2015 21:22	Dossier de fichiers
2015_04_23_M51_MarkII_AP F7.7	24/04/2015 22:10	Dossier de fichiers
2015_04_23_M65_M66_NGC3628_MarkII_AP F7.7	24/04/2015 22:06	Dossier de fichiers
2015_06_17_Nikon Ha_SM90	29/06/2015 14:49	Dossier de fichiers
2015_06_23_24_Nikon_VSD108	27/07/2015 13:02	Dossier de fichiers
2015_06_24_25_Nikon_5DVSD108	26/07/2015 18:36	Dossier de fichiers
2015_06_30_Conjonction Vénus_Jupiter	01/07/2015 17:04	Dossier de fichiers
2015_06_30_Iridium	01/07/2015 17:09	Dossier de fichiers

Dossier Images brutes Raw & JPG
 Dossier Dark
 Dossier Flat
 Dossier Bias

Bias MarkII	24/04/2015 22:05	Dossier de fichiers
Dark	24/04/2015 22:06	Dossier de fichiers
Flat	24/04/2015 22:12	Dossier de fichiers
Images brutes	07/07/2015 16:45	Dossier de fichiers

Paramétrage APN avec PixInsight

The screenshot shows the PixInsight 1.8 interface. The 'Format Explorer' on the left lists various file formats, with 'DSLR_RAW' selected. A context menu is open over the 'Integer Range' option, showing bit depths from 8-bit to 32-bit. The 'RAW Format Preferences' dialog is open on the right, with several options circled in red: 'Create raw Bayer CFA image', 'No image crop', 'No black point correction', 'No highlights clipping', 'Bilinear' interpolation, 'Automatic white balance', 'Camera white balance', and 'No white balance'. The 'Pure Raw' radio button is selected at the bottom of the dialog.

Option	Value / State
Integer Range	32-bit (4G)
Create raw Bayer CFA image	☒
No image crop	☒
No black point correction	☒
No highlights clipping	☒
Interpolation	Bilinear
White balance	Automatic white balance
White balance	Camera white balance
White balance	No white balance
Color adjustment	Pure Raw

Interface Pixinsight

PixInsight 1.8

FILE EDIT VIEW IMAGE PREVIEW

View Explorer
Format Explorer
File Explorer
Object Explorer
Script Editor
History Explorer

Process Console

```
C:/Program Files/PixInsight/bin/PixelMath.js
C:/Program Files/PixInsight/bin/Restoration.js
C:/Program Files/PixInsight/bin/SandB.js
C:/Program Files/PixInsight/bin/SplitTone.js
C:/Program Files/PixInsight/bin/Stargate.js
C:/Program Files/PixInsight/bin/TGV.js
C:/Program Files/PixInsight/bin/TIFF.js
C:/Program Files/PixInsight/bin/XISF.js
* Scripting resources updated.
46 of 46 module(s) installed.

Processing script file: C:/Program Files/PixInsight/bin/core-defs.js
* 1 initialization script(s) executed

Processing script file: C:/Program Files/PixInsight/etc/startup/startup.js
* 1 startup script(s) executed.

PixInsight Core 01.08.03.1123 Ripley (S)
Copyright (C) 2003-2014 Pleiades Astronomical Society
Welcome to PixInsight. Started 2016-08-10 10:00:00

* Parallel processing enabled: Using 4 threads
* Thread CPU affinity control enabled
* PSM AutoSave enabled. Auto-save period: 10 minutes
```

Ready

PROCESS SCRIPT WORKSPACE

<All Processes>

- BackgroundModelization
- ChannelManagement
- ColorCalibration
- ColorManagement
- ColorSpaceConversion
- ColorSpaces
- Compatibility
- Convolution
- Deconvolution
- Flux
- Fourier
- Geometry
- Global
- GradientDomain
- Image
- ImageCalibration
- ImageInspection
- ImageIntegration
- ImageRegistration
- IntensityTransformations
- MaskGeneration
- Morphology
- MultiscaleProcessing
- NoiseGeneration
- NoiseReduction
- Obsolete
- Painting
- PixelMath
- Preprocessing
- Render
- TotalGeneralizedVariation
- Wavelets
- <Etc>

- ACDNR
- AdaptiveStretch
- Annotation
- AssignICCProfile
- AssistedColorCalibration
- ATrousWaveletTransform
- ATrousWaveletTransformV1
- AutoHistogram
- AutomaticBackgroundExtraction
- B3Estimator
- BackgroundNeutralization
- Binarize
- Blink
- ChannelCombination
- ChannelExtraction
- ChannelMatch
- CloneStamp
- ColorCalibration
- ColorManagementSetup
- ColorSaturation
- CometAlignment
- ConvertToGrayscale
- ConvertToRGBColor
- Convolution
- CosmeticCorrection
- CreateAlphaChannels
- Crop
- CurvesTransformation
- Debayer
- Deconvolution
- DefectMap
- DigitalDevelopment
- Divide
- DrizzleIntegration
- DynamicAlignment
- DynamicBackgroundExtraction
- DynamicCrop
- DynamicPSF
- ExponentialTransformation
- ExtractAlphaChannels
- FastRotation
- FITSHeader
- FluxCalibration
- FourierTransform
- GradientHDRComposition
- GradientHDRCompression
- GradientMergeMosaic
- GREYCstorage
- HDRMultiscaleTransform
- HistogramTransformation
- ICCProfileTransformation
- ImageCalibration
- ImageIdentifier
- ImageIntegration
- IntegerResample
- InverseFourierTransform
- Invert
- LarsonSekanina
- LinearFit
- LocalHistogramEqualization
- LRGBCombination
- Mask
- Merge
- Morph
- MultiscaleProcessing
- NewImage
- NoiseReduction
- NoOp
- PixelMath
- Preferences
- Process
- Range
- Readout
- Resample
- Rescale
- Restore
- Rotational
- Sampling
- SandB
- SCNR
- Screen
- Script
- Simplify
- SplitChannels
- StarAlignment
- StarGrouping
- StarMasking
- Statistics
- Supernova
- TGVDrizzle
- UnsharpMask

Apply Process F5
Apply Global Process F6
Image Container Ctrl+Alt+I
Process Icons
Modules
Favorites

Batch Processing

Benchmarks

Coordinate Transformations

Development

Image Analysis

Instrumentation

Multichannel Synthesis

Render

Utilities

Run Script from Editor F9

Execute Script File...

Check Script File Syntax...

Feature Scripts...

Edit Scripts...

SCRIPT WORKSPACE WINDOW RESOURCES

- Batch Processing
 - Batch CMYK DeBayer
 - BatchChannelExtraction
 - BatchDeBayer
 - BatchFormatConversion
 - BatchLinearFit
 - BatchPreprocessing
 - BatchStatistics
 - SubframeSelector
- Run Script from Editor F9
- Execute Script File...
- Check Script File Syntax...
- Feature Scripts...
- Edit Scripts...

A l'aide !!!

Ou trouver les process icons, des méthodes, des tutos et de l'aide ?

Site PixInsight: <http://pixinsight.com/>

Association AIP: www.astro-images-processing.fr

Articles astronomie magazine: Nicolas Outters, Pierre Walcho
<http://outters.fr/wp/articles-astrosurf-magazine/>

Site Laurent Bourgon: <http://www.felopaul.com/>

Site Philippe Bernhard: <http://www.astro-photographie.fr>

Site Dominique Arnaud: <http://www.arnaudom.fr/pixinsight.php>

Coup d'œil sur les images brutes: Process Blink

Dans le fichier images brutes Raw + Jpg, sélectionner les images *.jpg

Les traces de satellites, avions,?? seront éliminées avec les réjections

Attention aux gradients changeant: diffusion éclairage, lune, etc..

Éliminer les défauts de suivi, turbulence, lumière accidentelle, etc..

[Lien Process Blink](#)

But du prétraitement des images

- ⦿ Extraire les parasites contenus dans l'image avec un logiciel de traitement adapté aux images du ciel

Image brute

Master Bias

Transfert de données

Master Dark

*bruit thermique:
pixels chauds et froids*

Master Flat

*défaut d'uniformité du capteur
poussières, interférences*

Créer un bias et le bonus « super bias »

Process Console

```
Total : 606318 0.246% ( 348488 + 257830 = 0.141% + 0.104%)
35.617 s

Debayer: Processing view: integration
CFA pattern: RGGB
WVG demosaicing: done
Noise evaluation: done
Gaussian noise estimates:
s0 = 1.162e-04, n0 = 0.5853 (MRS)
s1 = 1.121e-04, n1 = 0.7895 (MRS)
s2 = 1.162e-04, n2 = 0.5879 (MRS)
14.414 s

Debayer: Processing view: rejection_low
CFA pattern: RGGB
WVG demosaicing: done
Noise evaluation: done
Gaussian noise estimates:
s0 = 2.651e-05, n0 = 0.6883 (K-Sigma)
s1 = 4.287e-06, n1 = 0.6593 (K-Sigma)
s2 = 2.715e-05, n2 = 0.6858 (K-Sigma)
14.746 s

Superbias: Processing view: integration
Multiscale median transform: done
Multiscale reconstruction: done
Computing superbias columns: done
24.887 s

Ready
```

ImageIntegration

Input Images

- 1 ✓ 9Y2A5798.CR2
- 2 ✓ 9Y2A5799.CR2
- 3 ✓ 9Y2A5800.CR2
- 4 ✓ 9Y2A5801.CR2
- 5 ✓ 9Y2A5802.CR2
- 6 ✓ 9Y2A5803.CR2
- 7 ✓ 9Y2A5804.CR2
- 8 ✓ 9Y2A5805.CR2
- 9 ✓ 9Y2A5806.CR2
- 10 ✓ 9Y2A5807.CR2
- 11 ✓ 9Y2A5808.CR2

Format Hints

Image Integration

Combination: Average
Normalization: No normalization
Weights: Don't care (all weights = 1)
Weight keyword:
Scale estimator: Iterative k-sigma / biweight midvariance

Ignore noise keywords
 Generate integrated image
 Generate a 64-bit result image
 Generate drizzle data
 Evaluate noise
 Close previous images
Buffer size (MB): 32
Stack size (MB): 2018
 Use file cache

Pixel Rejection (1)

Rejection algorithm: Winsorized Sigma Clipping
Normalization: No normalization
 Generate rejection maps
 Clip low pixels
 Clip high pixels
 Clip low range
 Clip high range
 Report range rejection
 Map range rejection

Pixel Rejection (2)

Min/Max low: 1
Min/Max high: 1
Percentile low: 0.200
Percentile high: 0.100
Sigma low: 4.000
Sigma high: 4.400
Linear fit low: 5.000
Linear fit high: 2.500
Range low: 0.000000
Range high: 0.980000

Pixel Rejection (3)

Large-Scale Pixel Rejection
 Region of Interest

ScreenTransferFunction

```

Process Console
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Bias_MIII/9Y2A5800.CR2
3 : 55627 0.248% ( 18828 + 36799 = 0.084% + 0.164%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Bias_MIII/9Y2A5801.CR2
4 : 55073 0.246% ( 19214 + 35859 = 0.086% + 0.160%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Bias_MIII/9Y2A5802.CR2
5 : 55000 0.245% ( 19297 + 35703 = 0.086% + 0.159%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Bias_MIII/9Y2A5803.CR2
6 : 54706 0.244% ( 19213 + 35493 = 0.086% + 0.158%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Bias_MIII/9Y2A5804.CR2
7 : 55209 0.246% ( 19224 + 35985 = 0.086% + 0.160%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Bias_MIII/9Y2A5805.CR2
8 : 55428 0.247% ( 19201 + 36227 = 0.086% + 0.162%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Bias_MIII/9Y2A5806.CR2
9 : 55115 0.246% ( 19429 + 35686 = 0.087% + 0.159%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Bias_MIII/9Y2A5807.CR2
10 : 55265 0.246% ( 19405 + 35860 = 0.087% + 0.160%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Bias_MIII/9Y2A5808.CR2
11 : 55777 0.249% ( 19252 + 36525 = 0.086% + 0.163%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Bias_MIII/9Y2A5809.CR2
12 : 55078 0.246% ( 19329 + 35749 = 0.086% + 0.159%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Bias_MIII/9Y2A5810.CR2
13 : 55457 0.247% ( 19125 + 36332 = 0.085% + 0.162%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Bias_MIII/9Y2A5811.CR2
14 : 54958 0.245% ( 19213 + 35745 = 0.086% + 0.159%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Bias_MIII/9Y2A5812.CR2
15 : 55069 0.246% ( 19524 + 35545 = 0.087% + 0.158%)

Total : 828421 0.246% ( 288999 + 539422 = 0.086% + 0.160%)
54.091 s

```

Image du bias

Réjection 0,1 à 0,25%

Image super bias

Créer un master dark Calibrer les images sombres

The screenshot displays the PixInsight 1.8 interface. On the left, the 'Process Console' shows a list of executed steps, including 'open *file:///S:/Pretraitement_APN_AIP_PP_2018_10.xpsm*', 'Reading 1 File(s)', 'Calibration des Flats', 'Calibration des Images Brutes', 'Creation du MasterBias', 'Creation du MasterDark', 'Creation du MasterFlat', 'Preparation des Images', 'Alignement des Images', 'Integration Image Finale', 'Emplacement Final', 'Preparation a l'emplacement', 'Preparation des Masters', 'SuperBias', 'Debayer', 'SubFrameSelector', 'Integration des images alignees sans rejection', 'DynamicCrop', 'Debayesation Brutes Calibree', 'Integration Image Finale MIII', 'Integration Images Finales MIII', and 'Cosmetic Correction'. The 'Ready' status is shown at the bottom of the console.

The main window shows the 'Image Calibration' dialog. The 'Target Frames' list contains 8 items, all checked, with file names like 'YV2A6826.CR2'. The 'Format Hints' section shows 'Output directory:' and 'Sample format: 32-bit floating point'. The 'Pedestal' section has 'Master Bias' checked and 'Master Dark' and 'Master Flat' unchecked. The 'Optimization threshold' is set to 3.0000 and the 'Optimization window (px)' is 1024. The 'CFA pattern detection' is set to 'Detect CFA'. The 'Output' section shows the path 'D:/Documents/AFA/RCE/RCE_2018/PixInsight/Superbias_SDMIII_R3.8.fit'.

On the right, a vertical stack of process steps is visible, including 'Preparation des Masters', 'Creation du MasterBias', 'Calibration des Darks', 'Creation du MasterDark', 'Calibration des Flats', 'Creation du MasterFlat', 'Preparation des Images', 'Calibration des Images Brutes', 'Debayesation Brutes Calibree', 'Cosmetic Correction', 'SubFrameSelector', 'Alignement des Images', 'Preparation a l'emplacement', 'Integration des images alignees sans rejection', 'DynamicCrop', 'ImageContainer', 'Emplacement Final', 'Integration Image Finale', 'Integration Image Finale MIII', and 'Integration Images Finales MIII'.

Créer le master dark

Process Console

```
newImageProperties embedded: 'Observation:Time:Start', 12 bytes.  
** Warning: The output format cannot store view properties; existing  
properties have been stored as BLOB data.  
23 FITS keywords embedded.  
Writing FITS image: 32-bit floating point, 1 channel(s), 5796x3878  
pixels: done  
  
Writing output file: D:/Documents/AFA/RCE/RCE_2018/PixInsight/  
Images_Dark_MIII/9Y2A6844_c.fit  
Dark scaling factors:  
k0 = 1.000  
Gaussian noise estimates:  
s0 = 2.272e-04, n0 = 0.319 (MRS)  
** Warning: Deprecated file format: FITS  
BLOB property embedded: 'PCL:CFASourcePattern', 4 bytes.  
BLOB property embedded: 'Instrument:Camera:Name', 42 bytes.  
BLOB property embedded: 'Instrument:Camera:ISOspeed', 4 bytes.  
BLOB property embedded: 'Instrument:ExposureTime', 4 bytes.  
BLOB property embedded: 'Instrument:Telescope:Aperture', 4 bytes.  
BLOB property embedded: 'Observation:Time:Start', 12 bytes.  
** Warning: The output format cannot store view properties; existing  
properties have been stored as BLOB data.  
23 FITS keywords embedded.  
Writing FITS image: 32-bit floating point, 1 channel(s), 5796x3878  
pixels: done  
  
==== ImageCalibration: 14 succeeded, 1 failed, 0 skipped ====  
01:11.57
```

ImageIntegration

Input Images

- 1 ✓ 9Y2A6826_c.fit
- 2 ✓ 9Y2A6829_c.fit
- 3 ✓ 9Y2A6830_c.fit
- 4 ✓ 9Y2A6831_c.fit
- 5 ✓ 9Y2A6832_c.fit
- 6 ✓ 9Y2A6833_c.fit
- 7 ✓ 9Y2A6834_c.fit
- 8 ✓ 9Y2A6835_c.fit
- 9 ✓ 9Y2A6836_c.fit
- 10 ✓ 9Y2A6840_c.fit
- 11 ✓ 9Y2A6841_c.fit
- 12 ✓ 9Y2A6842_c.fit
- 13 ✓ 9Y2A6843_c.fit
- 14 ✓ 9Y2A6844_c.fit

Format Tests

Image Integration

Combination: Average
Normalization: No normalization
Weights: Don't care (all weights = 1)
Weight keyword:
Scale estimator: Iterative k-sigma / biweight midvariance

Ignore noise keywords
 Generate integrated image
 Generate a 64-bit result image
 Generate drizzle data
 Evaluate noise
 Close previous images

Buffer size (MiB): 32
Stack size (MiB): 2048

Pixel Rejection (1)

Rejection algorithm: Sigma Clipping
Normalization: No normalization
 Generate rejection maps
 Clip low pixels
 Clip high pixels
 Clip low range
 Clip high range
 Report range rejection
 Map range rejection

Pixel Rejection (2)

Min/Max low: 1
Min/Max high: 1
Percentile low: 0.100
Percentile high: 0.300
Sigma low: 4.000
Sigma high: 4.400
Linear fit low: 5.000
Linear fit high: 5.000
Range low: 1.000000
Range high: 0.980000

Pixel Rejection (3)

Large-Scale Pixel Rejection

Region of Interest

Coup d'œil sur l'image du master dark

Créer un master flat

Calibrer les images flat

The screenshot displays the PixInsight 1.8 interface. The main window shows the **ImageCalibration** dialog box, which is used for calibrating images. The **Target frames** list contains 9 frames, with the first three selected. The **Master Bias** checkbox is checked, and the **Master Dark** checkbox is unchecked. The **Master Flat** checkbox is also unchecked. The **Output Files** section shows the output directory and format settings. The **Process Console** on the left shows the results of the calibration process, including the total time and various statistics.

Process Console Output:

```
D:\Documents\AFA\RCE_2018\PixInsight\Images_Dark_MIII\9Y2A6836_c_fit
7 : 284 0.001% ( 0 + 284 = 0.000% + 0.001%)
D:\Documents\AFA\RCE_2018\PixInsight\Images_Dark_MIII\9Y2A6833_c_fit
8 : 291 0.001% ( 0 + 291 = 0.000% + 0.001%)
D:\Documents\AFA\RCE_2018\PixInsight\Images_Dark_MIII\9Y2A6840_c_fit
10 : 374 0.002% ( 0 + 374 = 0.000% + 0.002%)
D:\Documents\AFA\RCE_2018\PixInsight\Images_Dark_MIII\9Y2A6841_c_fit
11 : 365 0.002% ( 0 + 365 = 0.000% + 0.002%)
D:\Documents\AFA\RCE_2018\PixInsight\Images_Dark_MIII\9Y2A6842_c_fit
12 : 451 0.002% ( 0 + 451 = 0.000% + 0.002%)
D:\Documents\AFA\RCE_2018\PixInsight\Images_Dark_MIII\9Y2A6843_c_fit
13 : 582 0.002% ( 0 + 582 = 0.000% + 0.002%)
D:\Documents\AFA\RCE_2018\PixInsight\Images_Dark_MIII\9Y2A6844_c_fit
14 : 473 0.002% ( 0 + 473 = 0.000% + 0.002%)

Total : 4432 0.001% ( 0 + 4432 = 0.000% + 0.001%)
10.901 s

De Bayer: Processing view: integration2
CFA pattern: RGGB
VNG demosaicing: done
Noise evaluation: done
Gaussian noise estimates:
s0 = 7.919e-05, n0 = 0.2158 (MRS)
s1 = 7.627e-05, n1 = 0.3851 (MRS)
s2 = 7.813e-05, n2 = 0.2203 (MRS)
12.493 s

Ready
```

ImageCalibration Dialog Box Settings:

- Target frames:** 1-9 (1-3 selected)
- Output Files:** Output directory: [empty], Prefix: [empty], Postfix: `_c`, Sample format: 32-bit floating point, Output pedestal (DN): 0, Evaluate noise: checked, Noise evaluation: Multiresolution Support, On error: Continue
- Pedestal:** Pedestal mode: Default FITS keyword (PEDESTAL), Pedestal value (DN): 0, Pedestal keyword: [empty]
- Master Bias:** checked
- Master Dark:** unchecked
- Master Flat:** unchecked

ScreenTransferFunction: A window showing the color calibration curves for the image.

Créer un master flat

```
Process Console
4 : 34168 0.241% ( 29614 + 24534 = 0.155% + 0.109%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Flat_MIII/9Y2A6858 c.fit
5 : 42774 0.191% ( 20954 + 21820 = 0.093% + 0.097%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Flat_MIII/9Y2A6859 c.fit
6 : 38502 0.172% ( 15698 + 22804 = 0.070% + 0.102%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Flat_MIII/9Y2A6860 c.fit
7 : 39627 0.177% ( 18081 + 21546 = 0.081% + 0.096%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Flat_MIII/9Y2A6861 c.fit
8 : 34694 0.155% ( 14839 + 19855 = 0.066% + 0.089%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Flat_MIII/9Y2A6862 c.fit
9 : 42734 0.191% ( 16427 + 26307 = 0.073% + 0.117%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Flat_MIII/9Y2A6863 c.fit
10 : 119902 0.535% ( 49832 + 70070 = 0.222% + 0.312%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Flat_MIII/9Y2A6864 c.fit
11 : 25497 0.149% ( 16307 + 17190 = 0.073% + 0.077%)

Total : 601594 0.244% ( 72149 + 329445 = 0.110% + 0.134%)

MRS noise evaluation: done
Computing noise scaling factors: done

Gaussian noise estimates : 7.9109e-03
Scale estimates : 9.3915e-03
Location estimates : 2.2955e-02
SNR estimates : 8.6006e+00
Reference noise reduction : 0.9986
Median noise reduction : 0.9996

27.125 s

Ready [Pause/Abort]
```

Coup d'œil sur le Master flat

```
Process Console
4 : 34108 0.241% ( 29814 + 24534 = 0.153% + 0.109%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Flat_MIII/9Y2A6858 c.fit
5 : 42774 0.191% ( 20954 + 21820 = 0.093% + 0.097%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Flat_MIII/9Y2A6859 c.fit
6 : 38502 0.172% ( 15698 + 22804 = 0.070% + 0.102%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Flat_MIII/9Y2A6860 c.fit
7 : 39627 0.177% ( 18081 + 21546 = 0.081% + 0.096%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Flat_MIII/9Y2A6861 c.fit
8 : 34694 0.155% ( 14839 + 19855 = 0.066% + 0.089%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Flat_MIII/9Y2A6862 c.fit
9 : 42734 0.191% ( 16427 + 26307 = 0.073% + 0.117%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Flat_MIII/9Y2A6863 c.fit
10 : 119902 0.535% ( 49832 + 70070 = 0.222% + 0.312%)
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Images_Flat_MIII/9Y2A6864 c.fit
11 : 33497 0.149% ( 16307 + 17190 = 0.073% + 0.077%)

Total : 601594 0.244% ( 272149 + 329445 = 0.110% + 0.134%)

MRS noise evaluation: done
Computing noise scaling factors: done

Gaussian noise estimates : 7.9109e-03
Scale estimates : 9.3915e-03
Location estimates : 2.2955e-02
SNR estimates : 8.6606e+00
Reference noise reduction : 0.9986
Median noise reduction : 0.9996

27.125 s

Ready [Pause/Abort]
```

Dépouiller les parasites de l'image

- ⦿ Extraire les parasites contenus dans l'image avec un logiciel de traitement adapté aux images du ciel

Image brute

Master Bias
Transfert de données

Master Dark
*bruit thermique:
pixels chauds et froids*

Master Flat
*défaut d'uniformité du capteur
poussières, interférences*

Calibration des images brutes

Attention à la réjection ! Contrôle de la console Une bonne réjection se situe entre 0,1% et 0,25%
Modifier la valeur de Σ low et Σ high pour atteindre cette valeur

The screenshot displays the PixInsight 1.8 interface. On the left, the Process Console shows the following output:

```
Process Console
Gaussian noise estimates : 7.9189e-03
Scale estimates          : 9.3915e-03
Location estimates       : 2.2955e-02
SNR estimates            : 8.6697e+00
Reference noise reduction: 0.9986
Median noise reduction   : 0.9996

27.257 s

Writing file:
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Master_flat.xisf
Writing image: w=5796 h=3870 n=1 Gray Float32
112 FITS keyword(s) embedded.
Display function parameters embedded.

open file:///D:/Documents/AFA/RCE/RCE_2018/PixInsight/
Superbias_SDMIII_R3.8.fit*
Reading 1 file(s):
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Superbias_SDMIII_R3.8.fit
648 FITS keywords extracted.
Reading FITS image: 32-bit floating point, 1 channel(s), 5796x3870
pixels: done

Writing file:
D:/Documents/AFA/RCE/RCE_2018/PixInsight/Superbias_SDMIII_R3.8.xisf
Writing image: w=5796 h=3870 n=1 Gray Float32
648 FITS keyword(s) embedded.
Display function parameters embedded.

Ready
```

The central ImageCalibration dialog box is open, showing a list of target frames (9Y2A667...CR2) with checkboxes. The 'Master Bias', 'Master Dark', and 'Master Flat' sections are checked. The 'Output Format' section shows 'Sample format: 32-bit floating point'. The 'Pedestal' section shows 'Pedestal mode: Default FITS keyword (PEDESTAL)'. The 'Optimization' section shows 'Optimization window (px): 1024'. The 'CFA pattern detection' section shows 'Detect CFA'. The 'Screen TransferFunction' dialog box is also visible at the bottom right.

Process Debayer

Fichiers après Process Debayer: _d

Nom	Modifié le	Type	Taille
9Y2A6688_c_d.xisf	20/10/2018 21:44	Extensible Image S...	262 866 Ko
9Y2A6687_c_d.xisf	20/10/2018 21:44	Extensible Image S...	262 866 Ko
9Y2A6686_c_d.xisf	20/10/2018 21:44	Extensible Image S...	262 866 Ko
9Y2A6685_c_d.xisf	20/10/2018 21:44	Extensible Image S...	262 866 Ko
9Y2A6684_c_d.xisf	20/10/2018 21:43	Extensible Image S...	262 866 Ko
9Y2A6683_c_d.xisf	20/10/2018 21:43	Extensible Image S...	262 866 Ko
9Y2A6682_c_d.xisf	20/10/2018 21:43	Extensible Image S...	262 866 Ko
9Y2A6681_c_d.xisf	20/10/2018 21:43	Extensible Image S...	262 866 Ko
9Y2A6680_c_d.xisf	20/10/2018 21:43	Extensible Image S...	262 866 Ko
9Y2A6679_c_d.xisf	20/10/2018 21:43	Extensible Image S...	262 866 Ko
9Y2A6678_c_d.xisf	20/10/2018 21:42	Extensible Image S...	262 866 Ko
9Y2A6676_c_d.xisf	20/10/2018 21:42	Extensible Image S...	262 866 Ko
9Y2A6677_c_d.xisf	20/10/2018 21:42	Extensible Image S...	262 866 Ko
9Y2A6675_c_d.xisf	20/10/2018 21:42	Extensible Image S...	262 866 Ko
9Y2A6673_c_d.xisf	20/10/2018 21:42	Extensible Image S...	262 866 Ko
9Y2A6674_c_d.xisf	20/10/2018 21:42	Extensible Image S...	262 866 Ko
9Y2A6688_c.fit	20/10/2018 21:33	FITS Image File	87 666 Ko
9Y2A6687_c.fit	20/10/2018 21:33	FITS Image File	87 666 Ko
9Y2A6686_c.fit	20/10/2018 21:33	FITS Image File	87 666 Ko
9Y2A6685_c.fit	20/10/2018 21:33	FITS Image File	87 666 Ko
9Y2A6684_c.fit	20/10/2018 21:33	FITS Image File	87 666 Ko
9Y2A6683_c.fit	20/10/2018 21:33	FITS Image File	87 666 Ko
9Y2A6682_c.fit	20/10/2018 21:33	FITS Image File	87 666 Ko
9Y2A6681_c.fit	20/10/2018 21:33	FITS Image File	87 666 Ko
9Y2A6680_c.fit	20/10/2018 21:33	FITS Image File	87 666 Ko
9Y2A6679_c.fit	20/10/2018 21:33	FITS Image File	87 666 Ko
9Y2A6678_c.fit	20/10/2018 21:33	FITS Image File	87 666 Ko
9Y2A6677_c.fit	20/10/2018 21:33	FITS Image File	87 666 Ko
9Y2A6676_c.fit	20/10/2018 21:33	FITS Image File	87 666 Ko
9Y2A6675_c.fit	20/10/2018 21:32	FITS Image File	87 666 Ko
.....			

Process Cosmetic_Correction

Target Frames

1	✓	9Y2A6683_c_d_cc.xisf
2	✓	9Y2A6684_c_d_cc.xisf
3	✓	9Y2A6685_c_d_cc.xisf
4	✓	9Y2A6686_c_d_cc.xisf
5	✓	9Y2A6687_c_d_cc.xisf
6	✓	9Y2A6688_c_d_cc.xisf

Output

Output directory:

Prefix: Postfix:

CFA
 Overwrite

Amount:

Use Master Dark

Master Dark

Hot Pixels Threshold

Enable

Level:

Sigma:

Qty:

Real: Qty: 5068, Level: 0.0047760741, Sigma: 8.000978

Cold Pixels Threshold

Enable

Level:

Sigma:

Qty:

Real: Qty: 896788, Level: 0.0000000000, Sigma: 0.364857

Use Auto detect

Hot Sigma:

Cold Sigma:

Use Defect List

Real Time Preview

	Hot	Cold
Dark	0	0
Auto	0	0

Show map

Processing Steps:

- NOP Preparation des Masters
- Σ Creation du MasterBias
- Σ Creation MasterBias_RCE
- Calibration des Darks
- Σ Creation du MasterDark
- Σ Creation MasterDark_RCE
- Calibration des Flats
- Σ Creation du MasterFlat
- Σ Creation MasterFlat_RCE
- NOP Preparation des Images
- Calibration des Images Brutes
- Debayerisation Brutes_Calibree
- Cosmetic_Correction
- SubFrameSelector
- Alignement des Images
- NOP Preparation a l'empilement
- Σ Integration des images alignees sans rejection
- DynamicCrop
- ImageContainer
- NOP Empilement_Final
- Σ Integration_Image_Finale
- Σ Integration_Image_Finale_MIII
- Σ Integration_Images_Finales_MII

Comparatif des images

Image brute

Image calibrée

Identifier la meilleure image de la séquence: Process SubFrameSelector

Process StarAlignement pour aligner toutes les images

SubframeSelector

Target Subframes

- 1 9Y2A6673_c_d
- 2 9Y2A6673_c_d_cc
- 3 9Y2A6674_c_d
- 4 9Y2A6674_c_d_cc
- 5 9Y2A6675_c_d
- 6 9Y2A6675_c_d_cc
- 7 9Y2A6676_c_d
- 8 9Y2A6676_c_d_cc
- 9 9Y2A6677_c_d
- 10 9Y2A6677_c_d_cc
- 11 9Y2A6678_c_d

System Parameters

Star Detection and Fitting

Expressions

Table

Index Name (32 approved/32)	Weight	FWHM (pixel)	Eccentricity	SNRWeight
☒ 1 9Y2A6673_c_d	8.310	1.664	0.6952	8.310
☒ 2 9Y2A6673_c_d_cc	8.073	1.756	0.7045	8.073
☒ 3 9Y2A6674_c_d	8.475	1.598	0.6749	8.475
☒ 4 9Y2A6674_c_d_cc	8.167	1.685	0.6903	8.167
☒ 5 9Y2A6675_c_d	8.390	1.557	0.6734	8.390
☒ 6 9Y2A6675_c_d_cc	8.044	1.646	0.6907	8.044
☒ 7 9Y2A6676_c_d	8.427	1.559	0.6726	8.427
☒ 8 9Y2A6676_c_d_cc	8.093	1.654	0.6927	8.093

Plots

Ordinate: FWHM

Output

Version 1.11

Measure Output Subframes Output Maps Reset Dismiss

StarAlignment

Reference image: :s_brutes_MIII/9Y2A6675_c_d_cc.xisf

Distortion model: Undistorted reference

Registration model: Projective Transformation

Spline smoothness: 0.25

Distortion correction

Distortion residual: 0.005

Distortion iterations: 20

Working mode: Register/Match Images

Generate masks

Generate drizzle data

Frame adaptation

Target Images

- 1 9Y2A6673_c_d.xisf
- 2 9Y2A6673_c_d_cc.xisf
- 3 9Y2A6674_c_d.xisf
- 4 9Y2A6674_c_d_cc.xisf
- 5 9Y2A6675_c_d.xisf
- 6 9Y2A6675_c_d_cc.xisf
- 7 9Y2A6676_c_d.xisf
- 8 9Y2A6676_c_d_cc.xisf
- 9 9Y2A6677_c_d.xisf

Format Hints

Output Images

Output directory:

Prefix: Postfix: _r Mask: _m

Sample format: Same as target

Overwrite existing files On error: Continue

Star Detection

Star Matching

Interpolation

Process Intégration sans réjection pour éliminer les bordures noires. Process Dynamic Crop Image Container

Process image container

A screenshot of the PixInsight software interface. The main window displays a starry field. Overlaid on this are several panels:

- ImageContainer**: A panel with a list of image files. Below the list, it shows file details for item 16/16: "0:/Obs/2018_10_09_RA_dith_NGC7000_Pelican_MII/Prétraitement/IMG_0325_c_d_cc_r". Below that, the "Container Options" section is visible, with a gear icon circled in red.
- DynamicCrop**: A panel showing crop parameters: Width: 4416.00, Height: 3614.00, Anchor X: 2264.00, Anchor Y: 1847.00. It also shows rotation settings (Angle: 0.000) and scale options.
- Processors Panel**: On the right side, a vertical list of processors. The "Process25" processor at the bottom is circled in red.

Créer une image finale: Process Intégration Image_finale

Paramètres en fonction du nombre d'images

The screenshot displays the PixInsight software interface. On the left, the 'ImageIntegration' dialog box is open, showing a list of 16 input images. The 'Pixel Rejection (1)' section is highlighted with a red circle, showing 'Winsorized Sigma Clipping' as the rejection algorithm. The 'Normalization' dropdown is set to 'Scale + zero offset'. The 'Pixel Rejection (2)' section is also highlighted with a red circle, showing 'Sigma low' and 'Sigma high' both set to 4.000. The 'Pixel Rejection (3)' section is visible below. On the right, a workflow diagram shows a sequence of processing steps, including 'Preparation_des_Masters', 'Creation_du_MasterBias', 'Calibration_des_Darks', 'Creation_du_MasterDark', 'Creation_MasterDark_RCE', 'Calibration_des_Flats', 'Creation_du_MasterFlat', 'Creation_MasterFlat_RCE', 'Preparation_des_Images', 'Calibration_des_Images_Brutes', 'Debayerisation_Brutes_Calibree', 'Cosmetic_Correction', 'SubFrameSelector', 'Alignement_des_Images', 'Preparation_a_l_emploiement', 'Integration_des_images_alignees_sans_rejection', 'DynamicCrop', 'ImageContainer', 'Empilement_Final', 'Integration_Image_Finale', 'Integration_Image_Finale_MIII', and 'Integration_Images_Finales_MII'. A 'Screen TransferFunction: rejection_high' window is also visible at the bottom right, showing the RGB channels.

Créer une image finale: Process Intégration Image_finale

Paramètres en fonction du nombre d'images

Après le prétraitement, le traitement...

Gradients, déconvolution des étoiles, fond de ciel, calibration des couleurs, passage en mode non linéaire, correction de la couleur verte, réduction des étoiles, etc..

Où trouver les process icons, des méthodes, des tutos et de l'aide ?

Site PixInsight: <http://pixinsight.com/>

Association AIP: www.astro-images-processing.fr

Articles astronomie magazine: Nicolas Outters, Pierre Walcho
<http://outters.fr/wp/articles-astrosurf-magazine/>

Site Laurent Bourgon: <http://www.felopaul.com/>

Site Philippe Bernhard: <http://www.astro-photographie.fr>

Site Dominique Arnaud: <http://www.arnaudom.fr/pixinsight.php>

RCE Paris

1 – 3 novembre 2018

Prétraitement des images APN

Merci pour écoute